**Technical specification :**

Frequency range	: 42-30000 Hz +/-3 dB
Sensitivity (2.83V / 1m)	: 89 dB
Nominal impedance	: 4Ω
Max SPL	: 107 dB
Recommended amplifier	: 50-200 W
Cross-over frequency	: 2300 Hz
Speaker type	: 2½-way Floor Stand
Enclosure type	: Bass reflex
Port tuning frequency	: 35.5 Hz

Drive Units:

- High frequency driver : SATORI TW29BN
(Beryllium Tweeter)
- Low frequency drivers : 2 x 6½" SATORI MW16P-8
(advanced midwoofer)

Cabinet:

18 mm MDF


Dimensions (H x W x D) : 1009 x 190 x 464 mm / 45.87 x 12.41 x 20.47 inch

Net weight (pair):

- Cabinet only : 18.49 kg / 40.76 lb
- Full assembly : 22.42 kg / 49.43 lb

Special Features:

- Advanced high-end drivers
- Facets on top of cabinet for reduced high frequency diffraction
- Inclined baffle for correct time alignment of drivers (allowing for simpler cross-over design)
- Wedge shaped inner rear walls behind midwoofer for reduced direct reflection
- Internal bracing to reduce and distribute cabinet vibrations and hence lower sound coloration
- Dual ports for distribution of unwanted pipe resonances
- Inclined inner bottom for reduction of standing waves
- Solid single-wiring binding posts



Frequency response (Rinjani-Be)

