**Technical specification :**

Frequency range	: 42-25000 Hz +/-3 dB
Sensitivity (2.83V / 1m)	: 89 dB
Nominal impedance	: 4Ω
Max SPL	: 107 dB
Recommended amplifier	: 50-200 W
Cross-over frequency	: 3000 Hz
Speaker type	: 2½-way Floor Stand
Enclosure type	: Bass reflex
Port tuning frequency	: 35.5 Hz

**Drive Units:**

- |                         |                        |
|-------------------------|------------------------|
| - High frequency driver | SATORI TW29R           |
| :                       | (29 mm soft ring dome) |
| - Low frequency drivers | 2 x 6½" SATORI MW16P-8 |
|                         | (advanced midwoofer)   |

**Cabinet:**

18 mm MDF


Dimensions (H x W x D) : 1009 x 190 x 464 mm / 45.87 x 12.41 x 20.47 inch

**Net weight (pair):**

- |                 |                       |
|-----------------|-----------------------|
| - Cabinet only  | : 18.49 kg / 40.76 lb |
| - Full assembly | : 22.42 kg / 49.43 lb |

**Special Features:**

- Advanced high-end drivers
- Facets on top of cabinet for reduced high frequency diffraction
- Inclined baffle for correct time alignment of drivers (allowing for simpler cross-over design)
- Wedge shaped inner rear walls behind midwoofer for reduced direct reflection
- Internal bracing to reduce and distribute cabinet vibrations and hence lower sound coloration
- Dual ports for distribution of unwanted pipe resonances
- Inclined inner bottom for reduction of standing waves
- Solid single-wiring binding posts



Frequency response

